

Date:			
Туре:			
Project:			

## 2SBK4 / SBK4 WALL MOUNT

4" square wall mount made from aluminum extrusion. Designed for outdoor installation. Door frames are silicone gasketed for all-weather protection. Standard offering has wide beam light distribution that could be up or down light only (SBK4) or both up & down light (2SBK4). Check out other sizes under Exterior Surface Luminaires. Can also be installed indoors.





Name		Light Pattern	Light Engine	Lumens*	Color Temp	El	ectrical		Mounting
2SBK4 SBK4	U D	Up & down light Uplight only Down light only	9W LED per side (max)	1584	3000K 3500K 4000K 5000K	UNV HLV	120-277V 347-480V	WM	Wall mounted

	Lens Light Distribution		ht Distribution	Options			Finishes		
CG	Clear lens (Std)	WB	Wide beam (Std)	TP	Tamperproof hardware & screws	BL	Black		
FG	Frosted lens	MB	Medium beam	DM	0-10V Dimming	BZ	Bronze		
PG	Prismatic lens, K12	natic lens, K12 NB Narrow beam PC		Button photocell, voltage specific	WH	White			
				IP65	IP65 rated enclosure	SG	Silver Grey		
						BA4	Brushed Aluminum #4		
						CC	Custom Color		
						See finishes info on website			

<sup>\*</sup>General lumens are based on Wattage and 5000K CCT

Std – Standard Offering

2SBK4 or SBK4-		 -	 	 	 -

**Customization Notes:** 

<sup>\*</sup>Specific IES Files available upon request



## Dimensions & Mounting (measurements in inches; drawings are not to scale)



