


Solera CUSTOM ARCHITECTURAL LIGHTING • 1610 SISMET ROAD, MISSISSAUGA ON, L4W 1R4

Date:		
Туре:		
Project:		

DIX - BOLLARD

DESCRIPTION:

Constructed of aluminum housing. Silicone sealed gasketing for weather protection. Standard is monotone colored, optionally available with Metal Composite Material panels.



Name	Lamping	Source Lumens	Color Temp	Electrical			Mounting	
DIX-B	12W LED (Max)	2112	3000K	UNV	120-277V	ABT	Anchors, Bolts & Template	
			4000K	HLV	347-480V			
			5000K	TT	Tri-Tap (HID)			
				MT	Multi-Tap (HID)			
	*Contact for other wattages	*Contact for custom	*Specify other					

Lens		Light Pattern		Options		Finishes	
OPL	Opal Polycarbonate Lens (Std)	FT	Forward Throw	TP	Tamperproof Hardware	BL	Black
				TS	Tamperproof Screwdriver	WH	White
				DM	0-10V Dimming	SG	Silver Grey
				PC	Button Photocell	BZ	Bronze
				SF	Single Fuse	МСМ	Metal Composite Material
				НСО	House Side Cutoff		
						*S	ee finishes info on website

÷	Lumens	are	based	on	Max	Wattage	and	5000K	CCT

Std - Standard Offering


IES files available upon request


DIX-B	 	 	
ustomization Notes:			

>>> Info on this spec sheet will change without notice as product development is an ongoing process.



Dimensions & Mounting (drawings are not to scale)





Polar Graph

