

SONIC is designed tiered in order to mimic the undulating waves of sound. The coloured diffusive acrylic louvers are lit up subtly to provide a sophisticated effect while not compromising on light. The lenses can be configured in different ways and thicknesses with numerous color options and combinations.

CONSTRUCTION: Aluminum constructed frame work with 1/4" thick colored acrylic louvers (standard thickness).

MOUNTING:

P48 - 3/4" x 48" Long Pendant Stem with canopy for flat ceiling. Canopy mounts to standard recessed J-Box (by others).
 AC48 - 48" Long Aircraft Cable and ST cord with canopy for flat ceiling. Canopy mounts to standard recessed J-Box (by others).

LENS/SHIELDING:

LO - Acrylic louvers (1/4" thick), specify color after i.e. LO-GREEN
 OPL - Opal Acrylic Lens at Bottom

LAMPING OPTIONS: *SEE LAMPING CHART*

LINEAR FLUORESCENT:

T5HO - Miniature Bi-Pin holders provided to accept the T5 High Output Linear Fluorescent Lamps (by others)
 T8 - Bi-Pin holders provided to accept the T8 Linear Fluorescent Lamps (by others)

LED: High power CREE LED's with 50,000hrs rated lamp life @ 70% lumen maintenance.

Available in WHITE or RGB (Red, Green, Blue).
 Available with CREE XTE or COB (chip on board) technology. Contact Solera for detailed lumen packages.
 Available in:
 CW - Cool White, 5000-7000°K color temperature
 WW - Warm White, 3500°K color temperature
 NW - Neutral White, 4100°K color temperature.

ELECTRICAL:

Select from 120V, 277V, 347V
 (consult Solera for additional voltages)
 Electronic Driver/Ballast is standard on all LED, CFL, BIAx and Fluorescent lamps.

MOUNTING:

P48 - 3/4" x 48" pendant stem mounts with canopy to ceiling recessed J-Box (by others)
 AC48 - 48" Aircraft cable with ST cord mount with canopy to ceiling mounted J-Box (by others)
 CM - Ceiling Mounted to recessed J-Box (by others)
 SV - Swivel Canopy with Hang Straight Swivel Ball Aligner. C/W Aircraft cable in the middle point of stem for extra support.



OPTIONS:

Acrylic Louvers are available in a variety of colors (Red, Green, Blue etc.), sizes & design configurations. Standard louvers are 1/4" thick. Pendant options are available in clusters:
 Double, Triad, Quad (single is standard)

FINISH:

Electrostatically applied, thermally cured, polyester powder coated paint. Available in Solera standard colors on visible metal:
 BL - Minitex Black, WH - Minitex White, BZ - Minitex Bronze
 SG - Silver Gray


Clear, No Paint Options: BA4 - Brushed Aluminum #4
 ANO - Anodized Aluminum



WALL MOUNTED OPTION

	A	B	C	D	E
SONIC 26 (standard)	26"	30"	15"	17"	6"
SONIC 36 (F36T5HO)	36"	30"	15"	17"	6"
SONIC 48 (F54T5HO)	48"	30"	15"	17"	6"

CLUSTERS AVAILABLE:



LAMPING CHART BY LENGTH 'A'

	26"	36"	48"
LINEAR FLUORESCENT	4F17T8 4F24T5HO	4F36T5HO	4F54T5HO
LED	20LED	30LED	40LED

PROJECT DATE QTY

NAME	LAMPING	COLOR	VOLT	SHIELDING	MOUNTING	OPTIONS	FINISH
SONIC	*SEE LAMPING CHART*	TEMP. (LED)	120V 277V 347V 120/277V	LENS LO OPL	AC P48 CM	EM DM SF MS 2CC SV RGB DMX	WH BL SG BZ CC BA4 ANO

