

Date: _____

Type: _____

Project: _____

ARMAN WALL MOUNT

Contemporary wall mounted down light fixture with TYPE-II, TYPE-III, TYPE-IV light distribution.

Construction: Fixture housing constructed from aluminum alloy. Weatherproof silicon gasket seal for all weather protection. Stainless steel external hardware for corrosion resistance.

Mounting: Fixture is suitable to mount over octagonal J-box. (North America only)

Lens: Clear lens

Lamp: High power LEDs with 50,000 hrs. rated lamp life
L70% lumen maintenance
3000K, 3500K, 4000K, 5000K color temperature
CRI 80

Light distribution: Type II, Type III, Type IV

Driver: 60Hz, 120-277V / 347V electronic LED driver, thermally protected with low THD. 6kV native surge protection and 4kV EFT with Ambient Operating Temperature -40°C to 55°C.

Options: Photocell, 0-10V Dimming, 1% Dimming, Wet location


Finish: Black, White, Silver Gray, Bronze
(Custom color available upon request)

Listing: Complies with CSA & UL Standards, for indoor and outdoor location.


Warranty: [5-year limited warranty](#)




ARMAN-L:




ARMAN-S:




Distributions:



TYPE-II



TYPE-III



TYPE-IV

Additional options:



PHOTOCELL

--	--	--	--	--	--	--	--	--

Name	Light Engine	Color Temperature	Electrical	Mounting	Lens	Light Pattern	Options		Finish
ARMAN-S	20W LED (max)	3000K	UNV	WM-OCT	CPL	TY-II	DM	DM1	BL
ARMAN-L	60W LED (max)	3500K	HLV			TY-III	TP/TS	PC	BZ
		4000K				TY-IV	SF	WL	WH
		5000K							SG
									CC

Notes:

- 3000K – 152 lm/W
- 3500K – 153 lm/W
- 4000K – 160 lm/W
- 5000K – 160 lm/W
- UNV – Universal voltage (120V - 277V)
- HLV – High Low voltage (347V - 480V)
- WM-OCT – Wall mount over octagonal J-box (North America only)
- CPL – Clear lens
- SF – Single fuse
- TP/TS – Tamperproof hardware
- DM – 0-10V dimming
- DM1 – 1% dimming
- PC – Photocell (voltage specific)
- WL – Wet location
- BL – Minitex black
- BZ – Minitex bronze
- WH – Minitex white
- SG – Minitex silver gray
- CC – Custom color (Confirm RAL No. prior to production)