

Date: \_\_\_\_\_

Type: \_\_\_\_\_

Project: \_\_\_\_\_

## HAZE WALL MOUNT

The HAZE Wall Mount has slanted modern design with aluminum heatsink body. Its dark sky compliance and exposed LED light source makes it a stylish and efficient choice for area lighting with increased lumen efficiency.

**Construction:** Aluminum fixture housing features excellent heat dissipation with slanted shape to minimize water build-up. It is engineered to lessen glare enhancing visual comfort. All its external hardware is stainless-steel for corrosion resistance.

**Mounting:** The fixture housing mounts over octagonal J-box with four wall-mounting screws.

**Lamp:** High power LEDs with 50,000 hrs. rated lamp life L70% lumen maintenance 3000K, 3500K, 4000K, 5000K color temperature CRI 70

**Light distribution:** Type II, Type III, Type IV with or without house-side cut-off shield

**Driver:** 60Hz, 120-277V / 347-480V electronic LED driver, thermally protected with low THD. 6kV native surge protection and 4kV EFT with ambient operating temperature -40°C to 55°C.

**Options:** tamper-proof hardware, tamperproof bits, voltage-specific button photocell, 0-10v dimming


**Finish:** black, white, silver grey, bronze, custom color available upon request

**Listing:** complies with CSA & UL standards; label for outdoor location


**Warranty:** 5-year limited warranty



### HAZE-WM:



FRONT VIEW



SIDE VIEW

### Additional options:



HCO



PHOTOCELL

--	--	--	--	--	--	--	--

Name	Light Engine	Color Temperature	Electrical	Mounting	Light Pattern	Options	Finish
HAZE-WM	30W LED	3000K	UNV	WM	TY2	TP	BL
	60W LED	3500K	HLV		TY3	TS	BZ
		4000K			TY4	DM	WH
		5000K			TY2-HCO	PC	SG
		custom wattage available			TY3-HCO		CC
				TY4-HCO			

**Notes:**

- 3000K – 152 lm/w
- 3500K – 157 lm/w
- 4000K – 160 lm/w
- 5000K – 160 lm/w
- UNV – Universal voltage (120-277V)
- HLV – High low voltage (347-480V)
- WM – Wall mounted
- TY2 – Type II light distribution
- TY3 – Type III light distribution
- TY4 – Type IV light distribution
- HCO- House side cut-off shield
- TP – Tamperproof hardware
- TS – Tamperproof bits
- DM – 0-10V dimming
- PC – Voltage specific button photocell
- BL – Minitex black
- BZ – Minitex bronze
- WH – Minitex white
- SG – Minitex silver gray
- CC – Custom color (Confirm RAL No. prior to production)