

Date: _____

Type: _____

Project: _____

NEMO-BLD BOLLARD

Modern & simplistic with slanting design on the shaft. Body has smooth and sharp corners.

Construction: Fixture housing constructed from 6061 aluminum alloy. Weatherproof silicon gasket seal for all weather protection. Stainless steel external hardware for corrosion resistance.

Mounting: Aluminum base anchors to 4 flush-mounted bolts.

Lens: Opal lens

Lamp: High power LEDs with 50,000 hrs. rated lamp life L70% lumen maintenance
3000K, 3500K, 4000K, 5000K color temperature

Light distribution: Type V


Driver: 60Hz, 120-277V / 347V electronic LED driver, thermally protected with low THD. Operating temperature ranging between -10°C to 50°C.

Options: 0-10V Dimming, 10KV/20KV surge protector, ground fault receptacle, tamper-proof hardware, color changing LED, custom height (contact Factory)


Finish: Black, White, Silver Gray, Bronze
(Custom color available upon request)

Listing: Complies with CSA & UL Standards, Approved for indoor and outdoor location.

Warranty: [5-year limited warranty](#)



Anchoring Details:



Anchorbolt Size: 1/2" X 12" X 1-3/8"

- Hot dipped Galvanized anchor bolts
- Galvanized steel hex nuts
- Galvanized steel flat washers

