



Date
Quote #
Project Name
Type



VELO - Pendant

Description:

Constructed of fabricated aluminum and an opal acrylic lens. Rectangular cuboid design provides an encompassing glow pattern. All external hardware is stainless steel.

Name - Engine - Lumens - CCT - Electrical - Mounting - Lens - Pattern - Options - Finish

Name	Light Engine	Source Lumens _{(LED)(5000K)}	Color Temp	Electrical
VELO-24	24 18 LED (Max) F24T5HO	3168	2700K	UNV 120-277V
VELO-36	36 24 LED (Max) F36T5HO	4224	3000K	HLV 347-480V
VELO-48	44 44 LED (Max) F57T5HO	7744	3500K	
VELO-96	96 60 LED (Max) 2F57T5HO	10560	4000K	
	Contact for custom	Contact for custom	Contact for custom	

Mounting	Lens	Light Pattern	Options	Finishes
4AC48 4X48" aircraft cables	OAL Opal acrylic lens (Std)	EG Encompassing glow	DM 0-10V dimming	Aluminum frame only Standard
CM Ceiling mount			DM1 1% dimming	BL Black
			EM Emergency battery	WH White
			SF Single fuse	SG Silver Grey
			RGBW Programmable color changing LEDs	BZ Bronze
				Custom
				CC Custom Color
				See website for custom colors. Contact factory for physical samples.



- Lumens are based on max wattage & 5000K CCT
- IES files available upon request
- Std - Standard Offering





Dimensions & Mounting:

Please note that drawings are not to scale.



Listing:

Complies to CSA and UL standards.

Polar Graph:

